

## COVERBLOCK MOULDS CATALOGUE

**MULTI D**  
20x25x40x50



Regular

**MULTI D**  
20x25x40x50



Butterfly

**MULTI D**  
20x25x40x50



Large


**20 mm SINGLE**



**20x25x30x40**



**25 mm SINGLE**



**40 mm SINGLE**



**20x25 LIGHT**



**20x25 FLIP**



**20x25 MEDIUM**



**20x25 HEAVY**



**20x25x30**



**30x35**



**40x45**



**30x35x40**



**30x40**



**35x40x45x50**



**20mm ROUND**



**25mm ROUND**



**L - 40**



Internal Dia. : 13mm  
Thickness : 20mm

Internal Dia. : 13mm  
Thickness : 18mm

Thickness : 20mm

**30mm ROUND**



**40mm ROUND**



**40mm ROUND BIG**



**50 mm ROUND**



**50mm ROUND BIG**



**60 mm ROUND**



Internal Dia. : 13mm  
Thickness : 18mm

Internal Dia. : 13mm  
Thickness : 18mm

Internal Dia. : 17mm  
Thickness : 18mm

Internal Dia. : 13mm  
Thickness : 20mm

Internal Dia. : 14mm  
Thickness : 30mm

Internal Dia. : 17mm  
Thickness : 22mm

**75 mm ROUND**



**75 mm ROUND BIG**



**75 mm ROUND HEAVY**



**75 mm ROUND MEDIUM**



**100 mm ROUND**



**Ø150 mm ROUND**



Internal Dia. : 13mm  
Thickness : 26mm

Internal Dia. : 22mm  
Thickness : 24mm

Internal Dia. : 22mm  
Thickness : 50mm

Internal Dia. : 22mm  
Thickness : 35mm

Internal Dia. : 20mm  
Thickness : 40mm

Internal Dia. : 20mm  
Thickness : 35mm



Application of Footing Cover Block

<b>50 mm FOOTING</b>	<b>75 mm FOOTING</b>	<b>50 mm FOOTING PYRAMID</b>	<b>60 mm FOOTING PYRAMID</b>	<b>75 mm FOOTING PYRAMID</b>	<b>75mm Tower</b>
Internal Dia. : 10mm Thickness : 35mm	Internal Dia. : 10mm Thickness : 40mm	Draft : 60mm to 37mm	Draft : 65mm to 38mm	Draft : 74mm to 38mm	Internal Dia. : 8mm Thickness : 30mm

**KANDA 30x30**

	Cover Length
604 A	200 mm
604 B	230 mm
604 C	250 mm

**KANDA 40x40**

	Cover Length
605 A	300 mm
605 B	350 mm
605 C	400 mm

**KANDA 50x50**

	Cover Length
605 D	450 mm

<b>20mm Cylinder</b>	<b>25mm Cylinder</b>	<b>30mm Cylinder</b>	<b>40mm Cylinder</b>
			<b>Clips Sold Separately</b>

<b>25mm AST</b>	<b>30mm AST</b>	<b>40mm AST</b>	<b>50mm AST</b>	<b>60mm AST</b>	<b>75mm AST</b>
Thickness : 20mm	Thickness : 24mm	Thickness : 24mm	Thickness : 30mm	Thickness : 30mm	Thickness : 30mm

## WHAT IS A COVER BLOCK?

A Cover Block is essentially a spacer that is used to lift the rebar matrix off the ground so that concrete may flow under the rebar.

## WHY COVER BLOCKS ARE USED IN REINFORCEMENT?

Cover Blocks are used for the following reasons:

1. To maintain a specified distance between the rebar and the shuttering.
2. To protect the steel reinforcement bars from environmental effects to prevent their corrosion.
3. To provide thermal insulation, which protects the reinforcement bars from fire.
4. To give reinforcing bars sufficient embedding to enable them to be stressed without slipping.
5. Thus using cover blocks enhances the life of the structure significantly without adding much to the cost.

